

## Technical Data Sheet



### SELF ADHESIVE PAPER

|         |                                |                    |                           |
|---------|--------------------------------|--------------------|---------------------------|
| Product | Semi Gloss Self Adhesive Paper |                    |                           |
|         | Facestock                      | Adhesive           | Backing                   |
|         | 80gsm semi gloss art paper     | waterbased acrylic | 85gsm white release paper |

| Material                | Technical Name                                | Test Method | Unit             | Specifications |
|-------------------------|---|-------------|------------------|----------------|
| Facestock               | Basic Weight                                  | ISO536      | g/m <sup>2</sup> | 80±4           |
|                         | Caliper                                       | ISO534      | um               | 69±4           |
|                         | Whiteness                                     | ISO2470/1   | %                | 88-91          |
|                         | Opacity                                       | ISO2471     | %                | 88-91          |
|                         | Gloss   | T480        | %                | >65            |
| Adhesive                | Weight  | ISO536      | g/m <sup>2</sup> | 22±3           |
|                         | Initial Tack                                  | FTM9        | N/25mm           | >12            |
|                         | Tolding Tack                                  | FTM8        | H/25mm           | >2.5           |
|                         | Peel Adhesion<br>(180°C stainless steel 24Hr) | FTM1        | N/25mm           | >15            |
| Backing                 | Basic Weight                                  | ISO536      | g/m <sup>2</sup> | 85±5           |
|                         | Caliper                                       | ISO534      | um               | 97±5           |
| Labelling Temp          |   | >5°C        |                  |                |
| Service Temp            |   | -20~80°C    |                  |                |
| Self Life (23°C/50% RH) |   | 1 year      |                  |                |

#### Warranty:

This data is intended to be a guide to the values which may generally be expected, not constitute as a legal purpose. Since the final use of the product is outside our control, we strongly advise prior testing of its suitability for particular purpose.