

JINDA PRODUCTS DATA SHEET



Code: 0488022
Name: Clear PP 50um/AB600/Clear PET 30um

Facestock: Clear PP

Caliper:	50±5	um	TAPPI T411
Weight:	43+2	g/m ²	TAPPI T410
Gloss:	65	%	
Tensile Strength:	140	MD	ASTM D882
	277	CD	ASTM D882
Elongation at Break	202	MD	ASTM D882
	41	CD	ASTM D882

Roll Size:

Length: 500m-3000m
Full width: 1070mm

Printing / Converting

Applicable for letter press, flexo, offset, screen printing
Water based and UV inks are applicable
Testing prior to ink selection is always needed.
Roll tension should be controlled to avoid bleeding

Adhesive: AB600

Weight:	24±2	g/m ²	
Loop Tack:	≥9	N	FTM 9
Peel Adhes. 90°	≥6	N/25mm	FTM 2
Min. appl. Temp	0	°C	
Service temp.	-20 ~ 80	°C	

Stable and easy for die cut and dispense.

Suitable for a variety of labeling environment

Not recommend to apply on irregular substrates

Application

The product is suitable for a wide range of promotional and industrial label applications
Especially for beer and wine labels, cosmetics etc
No label look effect.

Storage:

Two year since produce time when stored at 20°C at 50% RH. Avoid direct sunlight and keep storage environment dry and ventilated,

Liner: Clear PET 30um

Weight:	42±2	g/m ²	ISO 536
Caliper:	30±5	um	ISO 534

It is primarily used for roll-to-roll label conversion and automatic labelling

Remark:

All statements, technical information and recommendations about JINDA products are based upon tests believed to be reliable but do not constitute a guarantee or warranty.
The product should be tested thoroughly under end-use conditions to ensure it meets the requirements of the specific application.