

UPM Raflatac Technical Information

13-03-2022 EN SI

Product	VELLUM BLUE-FSC / PERM.GREENTAC + / KRAFT SPECIAL 90 / SCORE UNPRINTED
Sales Code	BES/SP34/14/W2
Product use	Product designed for eye-catching display labels with variable information, such as price-marking, promotional and warning labels.

Typical technical values

Face	VELLUM BLUE-FSC
Product	Woodfree pulp dyed SC paper .
Substance	80 g/m ² ISO 536
Caliper	100 µm ISO 534
Tensile strength MD	4,8 kN/m ISO 1924/1
Tensile strength CD	2,5 kN/m ISO 1924/1
Roughness	6 µm ISO 8791 PPS 10
Opacity	90 % ISO 534 min.
Printability	Offset, flexography, letterpress, ink-jet, lasers and copiers.
Sustainability	The product is sold as FSC Mix Credit under UPM Raflatac's FSC™ certificate SGSCH-COC-004879.
Adhesive	SP34 GREENTAC PLUS
Type	General permanent adhesive for sheets.
Composition	Modified acrylic dispersion.
Use	A very good adhesive for general use with paper labels. Good heat resistance. Improved guillotine properties.
Tack min	10 N FTM 9
Shear min	2 h FTM 8
Limitations	Should not be used in cold environments. Not recommended for labeling highly curved surfaces.
Backing	KRAFT SPECIAL 90
Product	White woodfree kraft backing paper.
Substance	86 g/m ² ISO 536
Caliper	87 µm ISO 534
Tensile strength MD	8,7 kN/m ISO 1924
Tensile strength CD	3,8 kN/m ISO 1924
Performance	
Total caliper	203 µm
Minimum labelling temperature	5 °C
Service temperature	-10 to 100 °C

Shelf life

From date of manufacture: 48 months, under FINAT defined storage conditions (+20-25 °C and RH 40-50%). Prolonged storage at higher temperatures and/or humidity levels will shorten the shelf life.

Information

Product Information

Scoring is crucial to ensuring self-adhesive labels are easily peeled away from their backing. Our sheets have folding scores that are spaced at 35 mm intervals, what enables a smooth label opening. Scores open after bending 90–120° Scores don't open if they have not been folded previously.

Product availability

Standard range. (Other sizes and/or components available upon request).

STANDARD SHEET SIZE (CM)	50x70
PACKAGING TYPE	Ream wrapped / Bulk

Disclaimer

The performance of the product should always be tested in the actual application conditions. Our recommendations are based on our most current knowledge and experience. As our products are used in conditions beyond our control, we cannot assume any liability for damage caused through their use. Users of our products are solely responsible that the product is suitable for its intended application, and have determined such at their sole discretion. Users must comply with any applicable legislation and/or testing requirements for the finished article, and are responsible for bringing their products to market.

This publication does not constitute any warranty, express or implied, and is intended only for the recipient and cannot therefore be transferred to any third party. We cannot assume any liability for the use of our products in conjunction with other materials.

All our products are sold subject to UPM Raflatac's general sales conditions, and you should ensure that any existing laws are observed.

This publication replaces all previous versions. All information is subject to change without notice.

