

UPM Raflatac Technical Information

03-04-2020 EN SI

Face	THERMAL BOARD TOP 150
Sales Code	AZR
Product	A top side barrier coated board with a standard sensitivity thermal coating produced totally without BPA-based chemistry.
Use	Information labelling in dry environment e.g entrance tickets, parking receipts, hang and shelf tags, boarding passes etc.

Typical technical values

Substance	147	g/m ²	ISO 536	
Caliper	145	µm	ISO 534	
Brightness	70	%	ISO 2470/2	min
Smoothness	200	Bekk sec	ISO 5627	min
Imaging colour	Black			
Scanning	Visible red light			
Printability	Water-, UV- and solvent based flexography, UV letterpress, UV offset, screen, UV varnish. Direct thermal. For standard printers up to 250 mm/s.			
Storage recommendations	Store at a constant temperature (20°C, RH 50%) in the dark. Damp or hot conditions should be avoided.			
Disclaimer	The performance of the product should always be tested in the actual application conditions. Our recommendations are based on our most current knowledge and experience. As our products are used in conditions beyond our control, we cannot assume any liability for damage caused through their use. Users of our products are solely responsible that the product is suitable for its intended application, and have determined such at their sole discretion. Users must comply with any applicable legislation and/or testing requirements for the finished article, and are responsible for bringing their products to market.			

This publication does not constitute any warranty, express or implied, and is intended only for the recipient and cannot therefore be transferred to any third party. We cannot assume any liability for the use of our products in conjunction with other materials.

All our products are sold subject to UPM Raflatac's general sales conditions, and you should ensure that any existing laws are observed.

This publication replaces all previous versions. All information is subject to change without notice.